

# Product data sheet

NADJA IV (WALL FITTING)  
9.847.1032.05  
LEIPZIGER LEUCHTEN



Recommended mounting height 3.50 - 5.00 m, other heights please inquire. - High-quality mirror optics guarantee excellent illumination and glare protection - All designs to suit non-glare class KB1 - Aluminium luminaire body, inside white, outside painted in colour - Aluminium unit carrier, painted white - Special reflector made of highest grade aluminium, burnished, anodized - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Available in any RAL or DB colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

## Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	LOR	78%
Lamp flux	7200 lm	Total flux	5630 lm
Luminous efficacy	63 lm/W	Total power	89 W
CCT	3000 K		
CRI	90		

## Mounting mode

Wall mounted

## Shape and measurements

Height: 16.54 in  
Diameter: 16.54 in

## Design

Material impression: Matt

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 89 W  
Ballast: ECG

## Protection

IP: 55  
Designation labels: CE, ENEC

## Other operating numbers

Ambient temperature range: 32...95°F