


Product data sheet


PURE3.QUIET SUSP. ANTHR./WHITE L DI/ID HE PRISM
P33H34R-QAWSC2830H3T OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP
20


LED HO 3000K 254,2W 36523lm DALI CRI90 'Values without foil [Luminaire is delivered with optional satined-foil for increased homogeneity. The light distribution is thus influenced and the luminous flux is reduced by 7,3% <https://katalog.planlicht.com/en-gb/search?q=pure%203>

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	63.55 W	CRI	90
Total flux	9131 lm	LOR	100%
Luminous efficacy	144 lm/W	ULOR	34%
		Total power	63.55 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	63.55 W	CRI	90
Total flux	9131 lm	LOR	100%
Luminous efficacy	144 lm/W	ULOR	34%
		Total power	63.55 W

Light output 3 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	63.55 W	CRI	90
Total flux	9131 lm	LOR	100%
Luminous efficacy	144 lm/W	ULOR	34%
		Total power	63.55 W

Light output 4 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	63.55 W	CRI	90
Total flux	9131 lm	LOR	100%
Luminous efficacy	144 lm/W	ULOR	34%
		Total power	63.55 W

Mounting mode

Pendant

Shape and measurements

Length: 27.95 in

Width: 137.80 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 254.2 W

Protection

IP: 20