



Product data sheet

INFINITE PRO 1136MM SURFACE OPTICELL
AK14-24U8CLTWN3
LEDSC4




LedsC4 Infinite Pro 1136mm Surface Opticell AK14-24U8CLTWN3 Lineal lighting system for indoor use. For downlighting. Structure finish: Grey. Diffuser material: Polycarbonate. Diffuser finish: Opticell. Warranty: 5 Years. Product net weight (Kg): 2.48 Product length (mm): 1136 Product width or diameter (mm): 52 Product height (mm): 90 Class 1. IP: IP40. LED. No. of lampholders or LEDs: 1. LED brand: TRIDONIC. Driver brand: TRIDONIC. Maximum power of light source: 21.3W. Colour temperature: TW 2700-6500K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 16.6. Photobiological risk: RG1. % de Flickering: <4%. Real flux (lm): 3424. Real lm/W: 153. Voltage / frequency range: 220-240/50-60Hz. Voltage: 40. Equipment included: Yes. Total power: 22.4. Power factor: 0.97. Dimmable equipment included: DALI DT8 / PUSH.

Light output 1



1 x LED			
Nominal lamp power	22.48 W	LOR	100%
Lamp flux	3424 lm	Total flux	3423 lm
Luminous efficacy	152 lm/W	Total power	22.48 W
CCT	6500 K		
CRI	90		



1 x LED			
Nominal lamp power	22.48 W	LOR	100%
Lamp flux	3188 lm	Total flux	3188 lm
Luminous efficacy	142 lm/W	Total power	22.48 W
CCT	2700 K		
CRI	90		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 2.05 in

Width: 44.72 in

Height: 3.54 in

Adjustability

Fixed

Electric

System power: 22.48 W

Appliance Class: I

Protection

IP: 40