


# Product data sheet

PITTSFIELD 4 PENDANT LUMINAIRES  
PIT-90011-P-W40  
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour Temperature 3000K ,4000K - Diffuser for light output control O – Opal diffuser UGR <19 P – Micro-prismatic UGR <13 Modern design square shaped surface, recessed and pendant mounted ceiling luminaires with symmetrical up and down lighting for general or specialized lighting requirements. Lighting control system. - Wireless control employing the Bluetooth® 4.0 protocol controlled via Ligman's mobile App or physical control via xPress switch - Daylight and occupancy sensor options Extruded aluminium profile with 316 grade stainless steel fasteners. Opal or Micro-prismatic PMMA diffuser options for glare control. Built-in driver. Passive thermal management. Surface ceiling mountings with the use of steel support and screws. Pendant mounting with the application of adjustable steel suspension (1m) complete with electrical wires in white. Applications: private residences, offices schools and universities, retail, showrooms, galleries, museums, conference halls, meeting rooms, banks, bars, restaurants, hotel and similar installations

## Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	27.2 W	CRI	80
Total flux	3042 lm	LOR	100%
Luminous efficacy	112 lm/W	Total power	27.2 W

## Mounting mode

Pendant

## Shape and measurements

Length: 41.73 in  
Width: 8.39 in  
Height: 4.53 in  
Weight: 5.2 kg

## Adjustability

Free, Height adjustable

## Design

Color of housing: Black, White, Silver gray

## Glare protection

Glare protection: UGR < 19

## Electric

System power: 27.2 W  
Voltage: 230 V AC  
Ballast: ECG  
Controller: Dimmable 1..10V, DALI  
Appliance Class: I

## Integrated sensors

Integrated sensors: Daylight sensor, Motion sensor, Presence sensor

## Protection

IP: 20  
Surface temperature: 40°C  
Designation labels: CE, UL