


Product data sheet

ALBERTSLUND MINI POST LED 3000K 34W CLO
5747838721
LOUIS POULSEN



Albertslund Mini Post LED Design : Jens Møller-Jensen Concept : The fixture emits symmetrical glare-free light directed downwards. The top shade helps direct the light downwards and prevent light from being emitted upwards. The white painted reflectors result in diffuse and comfortable light distribution. Finish : Aluminium coloured with textured surface, graphite with textured surface or grey, powder coated. Material : Top shade: Form pressed glass fibre. Enclosure: Injection moulded clear polycarbonate. Anti glare ring: Injection moulded polycarbonate. Base: Die cast aluminium. Struts: Aluminium. Mounting : Pole dimension: Ø 60mm. Installation cable: 4m 3x1,5mm² (Class I) or 4m 2x1,5mm² (Class II). Terminal block: 1x3x2.5mm². Terminal block positioning: In fixture head. LED driver: In fixture head. Class : Ingress protection IP65. Electric shock protection I w. ground, II w/o ground. IK10. Weight : Max. 7,5kg.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	34 W	CRI	80
Total flux	2915 lm	LOR	100%
Luminous efficacy	86 lm/W	ULOR	15%
		Total power	34 W

Mounting mode

Pole top mounted

Shape and measurements

Height: 22.44 in

Diameter: 25.98 in

Adjustability

Fixed

Electric

System power: 34 W

Appliance Class: II

Protection

IP: 66

IK: 10