
Product data sheet


TEMPLED RAYLINE ECO V3 20 - DASY 5000K
6522XX2000XX5080XX
TEMPLED



IP 40 IK 08

LED-Linienleuchte (Baulänge: 1680 mm), modularer Gesamtaufbau mit austauschbaren Komponenten (Netzteil, LED-Lichtfeld, Lichtlenkungsoptik), Leistungsaufnahme: 20 Watt inkl. Vorschaltgerät, Lichtstrom: ca. 4.000 Lumen, Farbtemperatur: 5.000 K, Abstrahlwinkel: DASY (beidseitig asymmetrisch tiefstrahlend), Hochleistungslichtlenkungsoptik mit Kollimatorentechnik, Schutzart: IP40, 7-polige Durchgangsverdrahtung, Montagepunktabstand: 5040 mm, 5 Jahre Garantie, 10 Jahre Ersatzteilgarantie, Eingangsspannung AC: 198-240 VAC - 50/60 Hz, Eingangsspannung DC: 176-250 VDC, weitere Daten gemäß Produktblatt. Optional verfügbar: Weitere Farbtemperaturen: 2.700 K, 3.000 K, 6.500 K, Farbwiedergabeindex: CRI90, Schutzart IP44 oder IP55, DALI-Dimmung, Hochtemperaturvariante bis +70 Grad Celsius.

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	20 W	CRI	80
Total flux	4000 lm	LOR	100%
Luminous efficacy	200 lm/W	Total power	20 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 66.14 in
Width: 1.89 in
Height: 2.99 in

Design

Color of housing: Silver gray

Electric

System power: 20 W
Appliance Class: I

Protection

IP: 40
IK: 08

Other operating numbers

Ambient temperature range: -22...122°F