


Product data sheet

LINEDO_0,6M_60_1
950660.840.4M0.022
RZB




IP
54


IK
03

LINEDO, 9,5. 18 W, 1650. 3400 lm, 840, aluminium, on/off Continuous line luminaire, L 598 B 58 H 76


Light output 1




1 x LED			
Nominal lamp power	18 W	LOR	100%
Lamp flux	3400 lm	Total flux	3400 lm
Luminous efficacy	189 lm/W	Total power	18 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	16 W	LOR	100%
Lamp flux	2900 lm	Total flux	2900 lm
Luminous efficacy	181 lm/W	Total power	16 W
CCT	4000 K		
CRI	80		



1 x LED			
Nominal lamp power	11 W	LOR	100%
Lamp flux	2050 lm	Total flux	2050 lm
Luminous efficacy	186 lm/W	Total power	11 W
CCT	4000 K		
CRI	80		


**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

9.5 W
1650 lm
174 lm/W
4000 K
80

LOR
Total flux
Total power

100%
1650 lm
9.5 W

**1 x LED**

Nominal lamp power
Lamp flux
Luminous efficacy
CCT
CRI

14 W
2550 lm
182 lm/W
4000 K
80

LOR
Total flux
Total power

100%
2550 lm
14 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 2.28 in
Width: 23.54 in
Height: 2.99 in

Adjustability

Fixed

Electric

System power: 9.5-18 W

Protection

IP: 54
IK: 03