Product data sheet


48 CAMINO LED OUTDOOR LIGHT FITTING
48 3202A CL (48001 0224)
SCHUCH



IP 66 IK 09

LED outdoor light fitting, CAMINO, 45 W, 6670 lm, 148 lm/W, Class II, IP66, asymmetrical beam, 4000 K, CRI≥ 70, Ta -40 °C/+25 °C, L90>100000 h (@ Ta max), Pane Safety glass clear, Housing Die-cast aluminium, Colour grey, DB702N. LED outdoor light fitting of the GreenLine series with outstanding sustainable product design. Consisting of powder-coated die-cast aluminium housing, two-part. Upper part with ECG, LED modules, optics and frameless tempered safety glass pane, hinged and detachable from the lower part. Lower part with integrated pole mounting system, adjustable inclination, cable entry, strain relief and integrated pressure compensation system (dirt-resistant). Electro kit carrying all electrical components, completely removable by unplugging isolating plug connection. Zhaga LED modules with highly efficient optics, direct beam, Multi-Layer Technology. ECG with high surge protection, overload and short circuit protection. Universal die-cast aluminium pole mounting system for pole-top Ø 60/76mm and side-entry mounting Ø 42/60mm. Resource-saving and environmentally friendly thanks to interchangeability of components (no disposable light fitting). Length 610,00 mm, Width/Diameter 251,00 mm, Height 155,00 mm, Net weight 7,50 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	48 W	CRI	70
Total flux	6670 lm	LOR	100%
Luminous efficacy	139 lm/W	ULOR	7%
		Total power	48 W

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 24.02 in
Width: 9.88 in
Height: 6.10 in

Adjustability

Fixed

Electric

System power: 48 W
Appliance Class: I

Protection

IP: 66
IK: 09
Designation labels: CE, ENEC