
Product data sheet


LOUI 50
925334.003.1
RZB



IP 20 IK 02

Series: Less is more 50 Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Available Colours: jet black (RAL 9005) Type of Installation: Pendant Dimensions: L 1961, B 57, H 75 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: F-mark Impact Protection: IK02 (0,20 Joule) Luminaire flux LED: 8850lm System power: 74W Beam Angle: 104°/107° Number of fittings B10A: 7 Number of fittings B16A: 12 Number of fittings C10A: 12 Number of fittings C16A: 20 Inrush current: 34A Unified Glare Ratio: 23,6 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	74 W	CRI	80
Total flux	8850 lm	LOR	100%
Luminous efficacy	120 lm/W	ULOR	37%
		Total power	74 W

Mounting mode

Wall mounted

Shape and measurements

Length: 2.24 in
Width: 77.17 in
Height: 2.95 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 74 W

Protection

IP: 20
IK: 02