Product data sheet


HUBBLE DOUBLE 3 FLOOD 40º DIM PUSH 3000K WT
A2773231WT
ARKOSLIGHT



IP 20

Hubble is a recess-mounted LED with cardan joint type pivot, offering extremely outstanding lumen packages for spaces that require a large amount of light and spotlight type lighting. The capacity of Hubble to be directed without standing out from the ceiling, and its small size related to its lumens, help prevent the luminaire from generating an invasive presence in the area. Indicated for lighting from high ceilings and for retail, it has options to adjust the intensity of its high lumen flux.


Light output 1



1 x LED

Nominal lamp power	41 W	LOR	87%
Lamp flux	5000 lm	Total flux	4350 lm
Luminous efficacy	122 lm/W	Total power	41 W
CCT	3000 K		
CRI	90		

Light output 2



1 x LED

Nominal lamp power	41 W	LOR	87%
Lamp flux	5000 lm	Total flux	4350 lm
Luminous efficacy	122 lm/W	Total power	41 W
CCT	3000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 13.39 in
Width: 7.28 in
Height: 5.59 in

Adjustability

Cardanic

Electric

System power: 82 W

Protection

IP: 20

Design

Designer: Rubén Saldaña