
# Product data sheet


LIGHTING PAD R 600 INDIREKT
557-526
HÄFELE



IP 20

Extremely effective sound-absorbing acoustic luminaire, 3 cable holders on top, tool-free adjustable, embossed front fleece, colour grey dawn, diameter 696 mm, sound absorption class B, closed plastic cover on the reverse, 8 Bartenbach lenses integrated in the front fleece, indirect light component on top for additional ceiling lighting, 36 % direct, 64 % indirect beam, direct light component with narrow beam, CRI > 90, including converter and operating device, dimmable via DALI/switchDim, the dimming unit is capable for video conferencing, indirect light separately switchable when using 2 DALI addresses, please order suspension set with supply cord separately according to your individual mounting situation (length 2 m: 555-713, length 4 m: 555-714). Front fleece available in further colours: far mountain, nightfall, soft moss, vineyard, white, yellow field, black ink.

## Light output 1



1 x LED

| | | | |
|---|---|---|---|
| Nominal lamp power | 63.4 W | LOR | 101% |
| Lamp flux | 4620 lm | Total flux | 4683 lm |
| Luminous efficacy | 73 lm/W | Total power | 63.4 W |
| CCT | 3000 K | | |
| CRI | 92 | | |

### Mounting mode

Pendant

### Shape and measurements

Length: 0.04 in
Width: 0.04 in
Height: 0.04 in

### Adjustability

Fixed

### Design

Color of housing: Yellow, Red, Blue, White, Green, Anthracite / graphite

### Electric

System power: 63.4 W

### Protection

IP: 20