Product data sheet

SRT-SYSTEM IP20-SRGCB EP/1500 LED - GERÄTETRÄGER FIX CENTRAL.LINE.OPTIC | DEVICE MOUNT FIX CENTRAL.LINE.. 10000 865 DALI2 VW RAL 9016 (SRT+19510006800)


REGIOLUX



IP 20 IK 03

SRT-Quick-fit mounting system, Device mount, Modullänge/1500. Device mount made of a galvanised, profiled steel sheet; surface coated with polyester resin. Tool-free attachment with design-integrated pressure caps guarantee protection against theft and dismantling. Housing colour traffic white RAL 9016. Performance level: Economy Performance (EP) - For cost-sensitive projects, high efficiency and a long service life, Light distribution direct wide distribution by means of Central.Line.Optic of PMMA plastic, the lens optics ensure absolute ease of assembly and are simple to maintain thanks to the easily cleaned surface. The compact 1-row arrangement of the lenses ensures that the dots merge into a line with a homogeneous appearance in the object. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection by means of a fixed, 5-pin, quick-fit plug connector and a free choice of phases. Integrated guide for fast contacting. They are exchangeable, permit modernisation and reliably prolong the service life of the overall system. Dimensions (LxWxH): 1531mm x 55mm x 37mm Beam angle: 95°(C0)/100° (C90) Placement: LED, Colour rendering/Light colour CRI ≥ 80 / 6500K Colour tolerance: 3SDCM Photobiological safety (Luminaire): RG1 LED service life: 50000h L80/B10 (Tq 30°C), 50000h L90/B50 (Tq 30°C) Nominal luminous flux: 10386lm Luminaire luminous efficiency: 158lm/W Control gear: Electronic driver DALI2 (1 pcs.) System output: 66W Energy efficiency class/light source: C Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK03 (-20°C bis 30°C) Ambient temperatur: ta -20°C to 30°C Special properties: Ready for IoT UGR lat./long.: max. 23.5 / 24.8 Certification mark: IP20, Protection class I, ENEC10 VDE, F, HACCP DIN10500/Food/IFS-application-related suitability (see certificate)/BRC, Indoor, CE Warranty period: 5 years Regiolux GmbH Type: SRGCB EP /1500 LED 10000 865 DALI2 vw RAL 9016 Article number: 19510006800 Product deep link: https://www.regiolux.de/en/article/19510006800 General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	6500 K
Nominal lamp power	65.6 W	CRI	80
Total flux	10386 lm	LOR	100%
Luminous efficacy	158 lm/W	Total power	65.6 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 60.43 in
Width: 2.48 in
Height: 2.64 in

Electric

System power: 65.6 W
Appliance Class: 0

Protection

IP: 20
IK: 03
Designation labels: CE, ENEC

Design

Color of housing: White