


Product data sheet

PRELUDE BRUSHED STEEL 900LM 2700K RA>90
197340
SG ARMATUREN



Design: Hallvard Jakobsen Mirror luminaire with and without outlet behind lift-up lid. Luminaire made of metal and aluminium, and diffuser made of polycarbonate. Mounting as both concealed and visible installation, with flexible access to cables, and mounting in clips with option of additional wiring. Light distribution Direct Light technic LED 16W 2700K Ra>90 SDCM 3 L70/B10 >50,000 hrs Ta=25°C Control/Dimming Trailing edge dimming Protection Class I IP44 (mounted horizontally) / IP20 (mounted vertically) IK05 Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: Brushed Steel Optics: Acrylic Mounting/Connection Surface, Indoor Screwless terminal block Max. luminaires per circuit breaker: B10: 23, B16: 37, C10: 29, C16: 46

Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	16 W	CRI	90
Total flux	900 lm	LOR	100%
Luminous efficacy	56 lm/W	ULOR	24%
		Total power	16 W

Mounting mode

Wall mounted

Shape and measurements

Length: 20.08 in

Width: 3.15 in

Height: 2.76 in

Adjustability

Fixed

Electric

System power: 16 W

Appliance Class: I

Protection

IP: 20

IK: 05