



Product data sheet

SYSTEM BATTEN LUMINAIRE TRAQ CASE M1500 43W 5200LM CRI > 80
2008.5717 - TRAQ CASE INS M1500 LED5200-830 RB DALI E3H
REGENT



System batten luminaire Traq Case m1500, for mounting on Traq Linear mounting rail, with LED, system power: 43 W, standby power 0.5 W, luminous flux of luminaire 5200 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 72'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, direct light emission, opal, with translucent rectangular diffuser polycarbonate (PC), all-round beam, 1 integral control gear, DALI2, with emergency unit, for non-maintained and maintained mode, with self-test, complete with battery pack, (burning life 3h), with halogen-free wiring, support profile and system components to be ordered separately protection class I, ingress protection IP20, impact strength: IK 06, for ambient temperatures 0 to +30 °C, this product contains a light source of energy efficiency class B and EPREL registration number: 1249136 L = 1481 mm, B = 65 mm, H = 29 mm

Light output 1



1 x LED			
Nominal lamp power	51 W	LOR	100%
Lamp flux	5200 lm	ULOR	10%
Luminous efficacy	102 lm/W	Total flux	5201 lm
CCT	3000 K	Total power	43 W
CRI	80		

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Length: 58.31 in
Width: 2.56 in
Height: 0.94 in
Weight: 1.949 kg

Adjustability

Fixed

Electric

System power: 43 W
Appliance Class: I

Protection

IP: 20
IK: 06