



Product data sheet

CEILING AND WALL MOUNTED LUMINAIRE PURELITE 23W 3290LM CRI
2005.2568 - PURLT CW2131 LED3290-830 DALI
REGENT



Ceiling and wall mounted luminaire Purelite with LED, system power: 23 W, standby power 0.5 W, luminous flux of luminaire 3290 lm, colour rendering index CRI > 80, colour temperature 3000 K, warm white, colour tolerances SDCM 3, lifetime LED L80 75'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, omni-directional, incl. illumination of the ceiling, housing in aluminium, natural-colour anodised diffuser in synthetic material opal, 1 integral control gear, DALI, ENEC certified, Regent certified MINERGIE®-Modul luminaires S.A.F.E. 2019 (Re-0278), luminaire complies with the strict requirements for Minergie-certified luminaires protection class I, ingress protection IP20, glow wire test 650 °C, impact strength: IK 08, this product contains a light source of energy efficiency class B and EPREL registration number: 1124082 L = 2131 mm, B = 90 mm, H = 35 mm

Light output 1



1 x LED			
Nominal lamp power	29 W	LOR	100%
Lamp flux	3290 lm	ULOR	11%
Luminous efficacy	113 lm/W	Total flux	3290 lm
CCT	3000 K	Total power	23 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 83.90 in

Width: 3.58 in

Height: 1.38 in

Weight: 6.038 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 23 W

Appliance Class: I

Protection

IP: 20

IK: 08