


Product data sheet

HALO SURFACE SILVER 1360MM
R48A136-9006C1930L3S
PLANLICHT




LED LO 3000K 52W 3246lm DALI <https://katalog.planlicht.com/en-us/fam-halo/>

Light output 1 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	90
Total flux	406 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	6.5 W

Light output 2 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	90
Total flux	406 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	6.5 W

Light output 3 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	90
Total flux	406 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	6.5 W

Light output 4 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	90
Total flux	406 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	6.5 W

Light output 5 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	90
Total flux	406 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	6.5 W

Light output 6 (integrated)




Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	90
Total flux	406 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	6.5 W

Light output 7 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	90
Total flux	406 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	6.5 W

Light output 8 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	6.5 W	CRI	90
Total flux	406 lm	LOR	100%
Luminous efficacy	62 lm/W	Total power	6.5 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 53.54 in

Width: 53.54 in

Height: 2.52 in

Adjustability

Fixed

Electric

System power: 52 W

Protection

IP: 20

Designation labels: CE