
Product data sheet

ONDA2 A AV D1150 LED6000-830-60 LDE SR
42186320
ZUMTOBEL



Decorative LED Circular luminaire with textile cover for sound absorption for surface-mounting to ceilings, total power: 107 W, DALI controllable luminaire with LED converter; LED service life lasts 50000 h before luminous flux is reduced to 90% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 5895 lm, Luminaire efficacy: 55 lm/W. Colour rendering Ra > 80, colour temperature 3000 K to 6000K. aluminium housing in silver enamelled finish. Textile material fixed to frame. Includes electronic LED converter for DALI control. Luminaire wired with halogen-free leads Dimensions: Ø1150 x 105 mm weight: 18 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	107 W	CRI	80
Total flux	5895 lm	LOR	100%
Luminous efficacy	55 lm/W	ULOR	6%
		Total power	107 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.13 in
Diameter: 45.28 in
Weight: 18 kg

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 107 W
Voltage: 220-240 V AC
Controller: DALI