

Product data sheet


LSR2B, LSSQ2B LED 2" ROUND AND SQUARE CYLINDERS
LSSQ2B10SP159024D010 2LBDL WMH
COOPER LIGHTING



IP
47

Distributions: 15°, 25°, 40° and 55°, Mounting: ceiling, wall or stem, Extruded aluminum housing; Die-cast or spun aluminum reflectors, 6 color temperatures: 2400K, 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 500, 1,000 1,500 and 2,000, Colors: Matte Black, Matte White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

Light output 1 (integrated)



| | | | |
|--------------------|---------|-------------|--------|
| Lamp type | LED | CCT | 2400 K |
| Nominal lamp power | 10.3 W | CRI | 90 |
| Total flux | 391 lm | LOR | 100% |
| Luminous efficacy | 38 lm/W | Total power | 10.3 W |

Mounting mode

Ceiling recessed

Shape and measurements

Height: 0.39 in
Diameter: 2.00 in

Adjustability

Fixed

Electric

System power: 10.3 W

Protection

IP: 47