


# Product data sheet

FLAT POLYMERO KREIS SLIM

312084.002.4.19

RZB




IP  
40

IK  
10

Series: Flat Polymero Kreis Slim Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Master luminaire (MA), base: powder coated metal, cover fastening with push lock, cover opal plastic (PC), with HF movement sensor. - HF sensor 24 GHz with integrated corridor function - detection range 130° - functions are easy to set using 3 assigned push button switches - sensitivity/range 0.5-7m radially, adjustable from 10-100% - time control adjustable from 1 second to 15 minutes in 8 steps - daylight detection with 5 brightness levels and teach-in mode - up to 9 slave luminaires can be operated on one master luminaire (max. up to 150 W / 250 W) - only suitable for outdoor use to a limited extent, as it reacts sensitively to all movements. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 300, H 65 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 1300lm System power: 13W Beam Angle: 122° Number of fittings B10A: 129 Number of fittings B16A: 207 Number of fittings C10A: 129 Number of fittings C16A: 207 Inrush current: 0,1A Unified Glare Ratio: 20,4 EEC: A+

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	13 W	CRI	80
Total flux	1300 lm	LOR	100%
Luminous efficacy	100 lm/W	ULOR	12%
		Total power	13 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 2.56 in

Diameter: 11.81 in

## Adjustability

Fixed

## Electric

System power: 13 W

## Protection

IP: 40

IK: 10