



Product data sheet

PUNTO SINGLE RECESSED
00-7899-05-05
LEDSC4



LedsC4 Punto Single Recessed 00-7899-05-05 Pendant for indoor use. For downlighting. Structure material: Aluminium. Structure finish: Black. Warranty: 5 Years. Product net weight (Kg): 0.32 Product width or diameter (mm): 50 Product height (mm): 1500 Ø of the hole for recessing (mm): 65 Permitted ceiling thickness: 3-30 Class 2. Glow wire test: 850. IP: IP20. LED. No. of lampholders or LEDs: 1. LED brand: BRIDGELUX. Driver brand: HEP. Maximum power of light source: 5W. Colour temperature: 3000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 11.8. Photobiological risk: RG1. Real flux (lm): 329. Real lm/W: 51. Voltage / frequency range: 100-277/50-60Hz. Voltage: 8.5. Equipment included: Yes. Total power: 6.5. Power factor: 0.60. Dimmable equipment included: ON-OFF.

Light output 1



1 x LED			
Nominal lamp power	6.5 W	LOR	100%
Lamp flux	329 lm	Total flux	329 lm
Luminous efficacy	51 lm/W	Total power	6.5 W
CCT	3000 K		
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 1.97 in
Width: 1.97 in
Height: 1.97 in

Adjustability

Fixed

Electric

System power: 6.5 W
Appliance Class: II

Protection

IP: 20