

Product data sheet

STANDARD
501041.009.1
RZB




IP
44

IK
07

Series: Standard Type of Protection: IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Base: plastic. Two cable inlets. Cover: "textured glass, transparent. Protective cage: steel wire, galvanised;" screw mounting. Available Colours: grey Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 200, H 105 Lamp: LED Life time: 32000 h (L70/B50) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK07 (2 Joule) Luminaire flux LED: 470lm System power: 9W Beam Angle: 57°/62°/56°/21° Unified Glare Ratio: 20,7 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	9 W	CRI	80
Total flux	470 lm	LOR	100%
Luminous efficacy	52 lm/W	Total power	9 W

Mounting mode

Wall mounted

Shape and measurements

Height: 3.74 in
Diameter: 7.87 in

Adjustability

Fixed

Electric

System power: 9 W

Protection

IP: 44
IK: 07