



Product data sheet

STARTECH 2 BOLLARDS
ST-10356-W40
LIGMAN



- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Life time L90B10 Ta 25° 50,700 - Life time L80B10 Ta 50° > 63,500 - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - One IP68 connector supplied with 0.2 m of 3x1.0 sqmm outdoor cable - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Opal glass diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	41.2 W	CRI	80
Total flux	1031 lm	LOR	100%
Luminous efficacy	25 lm/W	ULOR	46%
		Total power	41.2 W

Mounting mode

Standing / Bollard

Shape and measurements

Length: 7.60 in

Width: 7.60 in

Height: 30.94 in

Weight: 8.9 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 41.2 W

Voltage: 230 V AC

Ballast: ECG

Controller: Dimmable 1..10V, DALI

Appliance Class: I

Protection

IP: 55

IK: 08

Surface temperature: 40°C