


Product data sheet

METEOR V2 LED COMPACT 4000 MICRO-PRM EDD 04 840 L-620MM
19.4367.2623.04
LUXIONA



Indoor luminaire. Assembly: surface mounted on ceiling. The body material is steel sheet. Colour - RAL 9005 (black). Dimensions: 620 x 209 x 64 mm. Diffuser: Micro-PRM (micro-prismatic diffuser PMMA). The efficiency of the optical system is 85,00%. Beam angle: (C0-C180) / (C90-C270) - 84,2° / 91,4°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 90000 h L80/B10. Luminaire luminous flux: 3934,3 lm. Power of luminaire: 24,9 W. Luminaire's light efficiency: 158 lm/W. Driver: DIM DALI (EDD). Voltage 220..240 V, 50..60 Hz. Power factor cosp: >0,95. Circuit load capacity: 17 (B10), 28 (B16), 26 (C10), 41 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP20. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



2 x LED			
Nominal lamp power	13.45 W	LOR	52%
Lamp flux	2317 lm	Total flux	2430 lm
Luminous efficacy	172 lm/W	Total power	26.9 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 24.41 in

Width: 8.23 in

Height: 2.52 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 26.9 W

Controller: DALI

Appliance Class: I

Protection

IP: 20

IK: 04

Other operating numbers

Ambient temperature range: 41...86°F