Product data sheet


BENTO AREA S
BENTO AREA-S V2-ASY14-12LED-2700K-5050-700 MA
RAGNI



IP 66

Made of aluminium and with symmetrical lines, Bento AREA is a functional floodlight with a minimalist design available in 3 sizes. Rectangular in shape, it has a compartment at the rear housing the control gear, which harmoniously joins the lighting section. It has a double compartmentalisation and is fully IP66. Fixed laterally with a lyre, it can be installed on crossbars and crowns as well as on the front. Bento AREA has 12 to 24 LEDs in the S version, 24 to 48 LEDs in the M version and 72 LEDs in the L version, with a colour temperature of 3000 K or 4000 K. It has optimised light distributions and is specially designed for sports lighting, car parks and tertiary areas. The Bento AREA luminaire incorporates the Zhaga standard in its design.

Light output 1



1 x LED

Nominal lamp power	26.7 W	LOR	100%
Lamp flux	3490 lm	Total flux	3490 lm
Luminous efficacy	131 lm/W	Total power	26.7 W
CCT	2700 K		
CRI	70		

Mounting mode

Pole top mounted

Shape and measurements

Length: 19.69 in
Width: 7.87 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 26.7 W

Protection

IP: 66