

Product data sheet

MATRIC 81MM SURFACE - A5
LA5JEE-840H-L890
LIGHTNET



LED surface-mounted luminaire. Direct only light distribution. Light channel made of aluminium profile with 81mm track width. Precise length production according to specifications possible. Surface natural anodised or white, graphite, black, champagne or copper coated. Further surface options see Lightnet-Surface-Collection or RAL of your choice. Microprismatic screen and satin louver with optimized glare limitation especially for office purposes. Opal diffuser made of acrylic glass for general lighting. Wallwasher for homogeneous vertical illuminance. Converter integrated into luminaire housing, optionally switchable or dimmable (1-10V, DALI, Touch-Dim, Casambi). Colour temperatures 2200K, 2700K, 3000K, 3500K, 4000K or 6500K. Binning initial ≤ MacAdam 3. Colour rendering CRI>80 or CRI>90. On request: Integration of emergency lighting components, sensor technology as well as many other options.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	29 W	CRI	82
Total flux	3080 lm	LOR	100%
Luminous efficacy	106 lm/W	Total power	29 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 35.04 in
Width: 3.19 in
Height: 3.19 in

Adjustability

Fixed

Electric

System power: 29 W

Protection