Product data sheet

ENØK/ECON LED BRUSHED STEEL 10W LED 3000K

5046187193

SG ARMATUREN





Round lamp in several sizes. Vandal-resistant with impact-resistant polycarbonate opalescent diffuser. The whole luminaire has been approved for common access routes and has vandal-resistant rating IK10. KI II, two cable inputs and the option of additional looping using the integrated guick clips. Can be mounted to either the wall or ceiling with both concealed and visible cabling. Many light source variants and sensors, wireless control and emergency light. Light distribution: Direct Light technic LED (exchangeable) 10W 3000K Ra>80 SDCM: 3 L70/B50 >50.000 hrs Ta=25°C Control/Dimming On/Off Phase cut-off Protection Class II IP44 IK10 Fire protection class: 850°C - 30s Energy and approvals A+ CE Materials and finish Housing: Aluminium Colour: White (RAL 9003) or Brushed Steel Optics: UV-stabilized polycarbonate Mounting/Connection Surface Screwless terminal block

Light output 1 (integrated)



Lamp type Nominal lamp power Total flux Luminous efficacy

LED 10 W 650 lm 65 lm/W

CCT	3000 K
CRI	80
LOR	100%
ULOR	6%
Total power	10 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 11.81 in Width: 11.81 in Height: 3.74 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 10 W Appliance Class: II

Protection

IP: 44 IK: 10