Product data sheet


VANCOUVER 24 SURFACE FACADE LUMINAIRES
VA-30001-W40
LIGMAN



IP 65 IK 08

- Lamp COB - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - High-efficiency optical reflector - Clear toughened glass - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	7.6 W	CRI	80
Total flux	325 lm	LOR	100%
Luminous efficacy	43 lm/W	ULOR	100%
		Total power	7.6 W

Mounting mode

Wall mounted

Shape and measurements

Length: 6.30 in
Width: 6.30 in
Height: 15.75 in
Weight: 6.4 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 7.6 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C