Product data sheet

OPALUME CAT OPAL SPHERICAL 21E9 740 CL1 CLO
306200-22946
FAGERHULT



IP 66

Installation Luminaire for wire installation, Ø 6-12 mm. The luminaire can be angled ±25°, in instances where the wire is not suspended horizontally over the roadway, and rotated ±130°, where the wire is not suspended perpendicular to the roadway. Connection Supplied without connecting cable but with prevision for a cable with an external diameter up to Ø 14 mm. Through-wiring possible. Luminaires can be supplied with a cable upon request. Design Diffuser of opal acrylic or spun aluminium in standard colors. Any color on request. Wire fastening in stainless steel. Heatsink and the rest of the wire mount are made of die-cast aluminium. Hardened flat glass. Fastener of A4 quality with zinc coating. Optics Specially developed L-lenses for installation in the middle of the road. The luminaire is also available with a rotationally symmetrical E-lens and other AGC (Advanced Glare Control) lenses if necessary. Adapt and optimise the luminaire in Fagerhult's configurator.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	129 W	CRI	70
Total flux	17566 lm	LOR	100%
Luminous efficacy	136 lm/W	Total power	129 W

Mounting mode

Pendant

Shape and measurements

Length: 19.96 in
Width: 19.96 in
Height: 17.20 in

Adjustability

Fixed

Electric

System power: 129 W

Protection

IP: 66