
Product data sheet


SANDY 9 SURFACE FACADE LUMINAIRES
SA-31553-O-TW2765
LIGMAN



IP 65 IK 08

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour TW(2700K - 6500K) - Die-cast aluminium housing and frame - Pre-treated before powder coating ensuring high corrosion resistance - Two cable entries for through wiring - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - Opal UV-stabilised polycarbonate diffuser - Optional surface mounting box for easy wiring or conduit connection when wiring from behind is not possible

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	28 W	CRI	80
Total flux	1180 lm	LOR	100%
Luminous efficacy	42 lm/W	ULOR	100%
		Total power	28 W

Mounting mode

Wall mounted

Shape and measurements

Height: 5.31 in
Diameter: 13.98 in
Weight: 4 kg

Adjustability

Fixed

Electric

System power: 28 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C