


Product data sheet

PLANOX
672199.009.3.89
RZB




IP
66

IK
08

Item Number: 672199.009.3.89 Series: Planox Type of Protection: IP 66 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: plastic polycarbonate, prepared for two suspension chains or cables (suspension provided on site), interior fastening element made of sheet steel, painted white, converter integrated, refractor plastic (polycarbonate), opal, prismatic inside, refractor attached using retaining clips made of stainless steel, with AC Control monitoring module for Luxifair central battery units. Lamp (LED) included. Available Colours: light grey (RAL 7035) Type of Installation: Ceiling mounting, Suspension cable/chain, Wall (surface) Dimensions: L 1278, B 96, H 100mm Lamp: LED Colour Temperature: 5000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Emergency Lighting System: AC-Control Safety Marks: D-mark, F-mark Impact Protection: IK08 (5 Joule) Luminaire flux LED: 5150lm System power: 42W Beam Angle: 136°/92° Unified Glare Ratio: 25,1 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	44 W	CRI	80
Total flux	5150 lm	LOR	100%
Luminous efficacy	117 lm/W	ULOR	7%
		Total power	44 W

Mounting mode

Wall mounted

Shape and measurements

Length: 3.78 in
Width: 50.31 in
Height: 3.94 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 44 W

Protection

IP: 66
IK: 08