
Product data sheet

X-LINE SLIGHT SPOTS UP&DOWN LED 5500/6600 PLX-T/PLX E / 2X 600 15° E 04 840 / L-1723MM S-1,5M TWO CIRCUIT
19.4401.342E.04


LUXIONA



IP 40 IK 04

Indoor luminaire. Assembly: surface mounted on slings. The body material is aluminum. Colour - RAL 9005 (black). Dimensions: 1723 x 34 x 68 mm. Diffuser: PLX-T/PLX (transparent PMMA/PMMA opal) [up/down] / optical system based on PMMA lenses. The efficiency of the optical system is 75,53%. Beam angle: (C0-C180) / (C90-C270) - 99,6° / 103° // (C0-C180) / (C90-C270) - 17,8° / 19,8°. Light source type: LED. Colour of the light 4000 K. SDCM=3. CRI>80. Lifetime of LED sources: 80000 h L80/B10. Luminaire luminous flux: 9951 / 1054 lm. Power of luminaire: 70,2 / 10,8 W. Luminaire's light efficiency: 141,8 / 97,6 lm/W. Driver: standard on/off (E) / standard on/off (E). Voltage 220..240 V, 50..60 Hz. Circuit load capacity: 8 (B10), 13 (B16), 11 (C10), 18 (C16). Operating temperature range: 5 ÷ 35° C. Protection degree: IP40. Impact resistant: IK04. Protection against electric shock: I. Photobiological risk class (IEC/EN 62471): RG0.

Light output 1



7 x LED

Nominal lamp power	10.029 W	LOR	52%
Lamp flux	1883 lm	Total flux	6912 lm
Luminous efficacy	188 lm/W	Total power	70.2 W
CCT	4000 K		
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 67.83 in
Width: 1.34 in
Height: 2.68 in

Adjustability

Fixed

Design

Color of housing: Black

Electric

System power: 70.2 W
Appliance Class: I

Protection

IP: 40
IK: 04

Other operating numbers

Ambient temperature range: 41...95°F