Product data sheet

ARCH ARCHEON SMALL COBRAHEAD ROADWAY LUMINAIRE

ARCH-S-PA1-50-740-U-T2R


COOPER LIGHTING



Die-cast aluminum construction; Single latch tool-less entry, Replaces up to 200W equivalent HID; -40°C to 40°C operating range, Polemounted; Optional arm and offset adjustable arm mounting, 120-277V 50/60Hz, 347V 60Hz or 480V 60Hz operation; IP66 rated, Lumens: 3,000 - 12,000; Up to 173 Im/W, 4000K standard; optional 2700K, 3000K, 5000K CCT; CRI: 70 standard, 6 high-efficiency, patented AccuLED Optics™ distributions, 10kV surge protection options; 3G vibration rated; 7-pin receptacle, Greater than 98% lumen maintenance after 60,000 hours at 40°C

IP 47

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	54 W	CRI	70
Total flux	7912 lm	LOR	100%
Luminous efficacy	147 lm/W	Total power	54 W

Mounting mode	Electric
Pole top mounted	System power: 54 W
Shape and measurements	Protection
Length: 6.00 in	IP: 47
Width: 9.00 in	
Height: 0.39 in	

Adjustability

Fixed