

Product data sheet

MAXITOMMASO


887154

FLOS



• Outdoor luminaire for installation on wall. • Configuration: die-cast aluminium structure . EN AB-47100 alloy (low copper content). • Double layer coating for high resistance to corrosion: The low copper Aluminium alloy is painted with a double coat using powders which are complaint with QUALICOAT standards: a first layer of epoxy powder (with excellent chemical and mechanical resistance) and a second finishing layer of polyester powder (resistant to UV rays and atmospheric agents).The entire painting process of the aluminium fitting starts from components which have been sand-blasted in advance to make the surface more porous and increase the adherence of the paint. Ares effects alkaline and acid washing to clean the surfaces completely, then rinses with demineralised water to remove any residue particles, subsequently a chemical conversion treatment is done to protect against rusting. • Tempered sandblasted glass; convex lens (MaxiTomaso); silicone gasket.

Light output 1



1 x Metal halide lamp			
Nominal lamp power	70 W	Socket	G12
Lamp flux	7000 lm	LOR	29%
Luminous efficacy	29 lm/W	ULOR	5%
CCT	3000 K	Total flux	2047 lm
CRI	84	Total power	70 W

Mounting mode

Wall mounted

Shape and measurements

Length: 14.17 in

Width: 4.33 in

Height: 4.72 in

Adjustability

Fixed

Electric

System power: 70 W

Appliance Class: I

Protection

IP: 65

IK: 08