

Product data sheet


FLOW 1 HIT-DE 70W GY
111320 HIT
DEFA LIGHTING



IP
66


Flow 1 er en robust lyskaster med et bredt bruksområde for metallhalogen og høytrykk natriumlampe.

Light output 1




1 x Metal halide lamp

Nominal lamp power	70 W	Socket	Rx7S
Lamp flux	6300 lm	LOR	69%
Luminous efficacy	51 lm/W	Total flux	4337 lm
CCT	3976 K	Total power	85 W
CRI	65		




1 x Metal halide lamp

Nominal lamp power	70 W	Socket	Rx7S
Lamp flux	6600 lm	LOR	69%
Luminous efficacy	53 lm/W	Total flux	4543 lm
CCT	3000 K	Total power	85 W
CRI	65		



1 x Metal halide lamp

Nominal lamp power	70 W	Socket	Rx7S
Lamp flux	6200 lm	LOR	69%
Luminous efficacy	50 lm/W	Total flux	4268 lm
CCT	3000 K	Total power	85 W
CRI	65		



1 x Metal halide lamp

Nominal lamp power	70 W	Socket	Rx7S
Lamp flux	6500 lm	LOR	69%
Luminous efficacy	53 lm/W	Total flux	4474 lm
CCT	4200 K	Total power	85 W
CRI	95		

Mounting mode

Pole top mounted, Wall mounted

Shape and measurements

Length: 14.57 in
Width: 11.02 in
Height: 4.72 in

Adjustability

Tiltable

Electric

System power: 85 W

Protection

IP: 66