


Product data sheet

CIRCULAR OUTWARD 4 RINGS (Ø600 Ø1200 Ø1200 Ø600)
CF4J-00W9AZOU05
LEDSC4




LedsC4 Circular Outward 4 Rings (Ø600 Ø1200 Ø1200 Ø600) CF4J-00W9AZOU05V1 Pendant for indoor use. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 13 Product width or diameter (mm): 1177 Product height (mm): 5500 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 207.6W. Colour temperature: 3000K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. Real flux (lm): 18130. Real lm/W: 84. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 216. Power factor: 0.90. Dimmable equipment included: ON-OFF.

Light output 1




1 x LED			
Nominal lamp power	37.9 W	LOR	100%
Lamp flux	3402 lm	ULOR	50%
Luminous efficacy	90 lm/W	Total flux	3403 lm
CCT	3000 K	Total power	37.9 W
CRI	90		

Light output 2




1 x LED			
Nominal lamp power	37.9 W	LOR	100%
Lamp flux	3402 lm	ULOR	50%
Luminous efficacy	90 lm/W	Total flux	3403 lm
CCT	3000 K	Total power	37.9 W
CRI	90		

Light output 3



1 x LED			
Nominal lamp power	70.1 W	LOR	100%
Lamp flux	5663 lm	ULOR	49%
Luminous efficacy	81 lm/W	Total flux	5664 lm
CCT	3000 K	Total power	70.1 W
CRI	90		

Light output 4



1 x LED			
Nominal lamp power	70.1 W	LOR	100%
Lamp flux	5663 lm	ULOR	49%
Luminous efficacy	81 lm/W	Total flux	5664 lm
CCT	3000 K	Total power	70.1 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 23.62 in
Width: 23.62 in
Height: 1.18 in

Adjustability

Fixed

Electric

System power: 216 W
Appliance Class: I

Protection

IP: 20