Product data sheet


SLOIN ID CL LED1600-830 L793 LDE WH
42185891
ZUMTOBEL



IP 20


Corner luminaire for LED light line DI with DALI-controllable LED converter; LED service life lasts 50000 h before luminous flux is reduced to 70% of the initial value. Chromaticity tolerance (initial MacAdam): 3. Luminaire luminous flux: 6240 lm, Luminaire efficacy: 125 lm/W. Colour rendering Ra > 80, colour temperature 3000 K. Luminaire of aluminium, white powder coated. Luminaire uniformly bright over 100% of the surface. Luminaire consists of housing, gear tray and wiring. Luminaire wired with halogen-free leads. Degree of protection: IP20. Dimensions: 793 x 76 x 109 mm weight: 8 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	25 W	CRI	80
Total flux	3120 lm	LOR	100%
Luminous efficacy	125 lm/W	ULOR	69%
		Total power	25 W

Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	25 W	CRI	80
Total flux	3120 lm	LOR	100%
Luminous efficacy	125 lm/W	ULOR	69%
		Total power	25 W

Mounting mode

Pendant

Shape and measurements

Length: 31.22 in
Width: 2.99 in
Height: 4.29 in
Weight: 8 kg

Electric

System power: 50 W
Voltage: 220-240 V AC
Controller: DALI

Protection

IP: 20

Design

Material impression: Aluminum

Color of housing: White