


# Product data sheet

POPPACK LED6000-840 HFI E3 L1500


96643385

THORN LIGHTING




Batten LED luminaire with replaceable light engine. Electronic, DALI dimmable Local battery luminaire, manual test (3 hours). Body: coated, formed steel, white (RAL9016). End caps: injection moulded polycarbonate, white. Diffuser: textured opal acrylic. Electrical connection via (4 + 2) x 2 x 2.5mm<sup>2</sup> terminal block. Complete with 4000K LED Dimensions: 1449 x 60 x 74 mm Total power: 58.9 W Luminaire luminous flux: 6300 lm Luminaire efficacy: 107 lm/W Weight: 2.3 kg

## Light output 1 (integrated, emergency)



Lamp type	LED	CCT	3000 K
Nominal lamp power	0.01 W	CRI	80
Total flux	350 lm	LOR	100%
Luminous efficacy	35000 lm/W	ULOR	17%
		Total power	0.01 W

## Light output 2 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	58.9 W	CRI	80
Total flux	6300 lm	LOR	100%
Luminous efficacy	107 lm/W	ULOR	17%
		Total power	58.9 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 57.05 in

Width: 2.36 in

Height: 2.91 in

Weight: 2.3 kg

## Design

Color of housing: White

## Electric

System power: 58.91 W

Voltage: 220-240 V AC

Controller: DALI

Appliance Class: I

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Protection

IP: 20

IK: 03

Designation labels: CE