

# Product data sheet

HBYS L80 LE3  
HALOBAY SURFACE LED EMERGENCY  
DEXTRA




IP  
20




Halobay Surface Surface mounted luminaire, spun aluminium housing, high transmission opal polycarbonate dished diffuser. Options: LE3 - Lithium Emergency (593 lumens output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) RLS - Reacta-Link Wireless Presence

## Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	45.1 W	CRI	80
Total flux	7360 lm	LOR	100%
Luminous efficacy	163 lm/W	ULOR	4%
		Total power	45.1 W

## Light output 2 (integrated, emergency)



Lamp type		CCT	4000 K
Nominal lamp power	4.5 W	CRI	80
Total flux	593 lm	LOR	100%
Luminous efficacy	132 lm/W	ULOR	4%
		Total power	4.5 W

## Mounting mode

Ceiling mounted

## Shape and measurements

Height: 2.48 in

Diameter: 21.65 in

## Adjustability

Fixed

## Electric

System power: 49.6 W

Ballast: ECG

## Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

## Protection

IP: 20

Designation labels: CE