


Product data sheet

DILED IV PRISM 300X1200 WHITE 3830LM 4000K RA>80 DALI
5703821179386
SG ARMATUREN



DiLED IV Linear is a recessed mounted luminaire for most known ceiling systems in different modules. DiLED IV Linear is suitable for office and general indoor lighting. The opal/prismatic optic front ensures a uniformly lit surface. Complete with driver and quick connection between driver and luminaire for super fast and easy mounting. Supplied with different color temperatures with on/off or Dali control. Emergency units for easy connection to the luminaire as extra accessories. Light technic LED 33W 4000K Ra>80 SDCM 3 L85/B10 >100,000 hrs at Ta=25°C Control/Dimming DALI Protection Class II IP20 Energy and approvals A++ CE Materials and finish Housing: Sheet steel Colour: White Optics: PMMA Polymethylmethacrylat Mounting/Connection Recessed, Indoor 300x1200 Exposed T-carrier 15/24mm Screwless terminal block Max. luminaires per circuit breaker: B10: 35, B16: 55, C10: 51, C16: 94

Light output 1



1 x LED			
Nominal lamp power	33 W	LOR	100%
Lamp flux	3830 lm	Total flux	3830 lm
Luminous efficacy	116 lm/W	Total power	33 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 46.93 in

Width: 11.50 in

Height: 2.54 in

Adjustability

Fixed

Electric

System power: 33 W

Appliance Class: II

Protection

IP: 20