Product data sheet


CIRCULAR INWARD 5 RINGS (Ø600 Ø1200 Ø2000 Ø1200 Ø600)
CD4F-00A9AZOU14
LEDSC4



IP 20

LedsC4 Circular Inward 5 Rings (ø600 ø1200 ø2000 ø1200 ø600) CD4F-00A9AZOU14V1 Pendant for indoor use. Structure finish: White. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 0 Product width or diameter (mm): 2074 Product height (mm): 5500 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 330.8W. Colour temperature: 2400K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG0. Real flux (lm): 16531. Real lm/W: 49. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 340. Power factor: 0.90. Dimmable equipment included: ON-OFF.


Light output 1



1 x LED

Nominal lamp power	37.4 W	LOR	100%
Lamp flux	2007 lm	ULOR	50%
Luminous efficacy	54 lm/W	Total flux	2007 lm
CCT	2400 K	Total power	37.4 W
CRI	90		


Light output 2



1 x LED

Nominal lamp power	37.4 W	LOR	100%
Lamp flux	2007 lm	ULOR	50%
Luminous efficacy	54 lm/W	Total flux	2007 lm
CCT	2400 K	Total power	37.4 W
CRI	90		


Light output 3



1 x LED

Nominal lamp power	69.3 W	LOR	100%
Lamp flux	3345 lm	ULOR	50%
Luminous efficacy	48 lm/W	Total flux	3345 lm
CCT	2400 K	Total power	69.3 W
CRI	90		


Light output 4



1 x LED

Nominal lamp power	126.6 W	LOR	100%
Lamp flux	5827 lm	ULOR	50%
Luminous efficacy	46 lm/W	Total flux	5827 lm
CCT	2400 K	Total power	126.6 W
CRI	90		

Light output 5



1 x LED

Nominal lamp power	69.3 W	LOR	100%
Lamp flux	3345 lm	ULOR	50%
Luminous efficacy	48 lm/W	Total flux	3345 lm
CCT	2400 K	Total power	69.3 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 23.62 in

Width: 23.62 in

Height: 1.18 in

Adjustability

Fixed

Electric

System power: 340 W

Appliance Class: I

Protection

IP: 20