Product data sheet

SCON-S AC 250 LED650-927 SP CR
60510254
ZUMTOBEL

Spherical pendant luminaire; sphere of polycarbonate with semi-transparent, reflective chrome-plated finish; lighting impact: semi-transparent reflection of light creates sense of plasticity and depth; lamp(s): LED650-927, Luminaire or spotlight with SPOT light distribution (17 °); Colour rendering Ra > 90, colour temperature 2700 K (warm white); Chromaticity tolerance (initial MacAdam): 3; Luminaire luminous flux: 650 lm, Luminaire efficacy: 72 lm/W; service life: 50000h for luminous flux at 80% of initial value; UV-free and IR-free light; modular, high quality optical unit consisting of reflector and LED light chamber; passive thermal management achieved by optimised design of luminaire housing; reflector made of high-quality, UV-resistant polycarbonate, highly reflective aluminized finish, iridescence-free; electronic control gear , integrated in ceiling rose; ceiling rose of polycarbonate, chrome matt; transparent pendant cord; electrical connection: 3-pole connector terminal; total power: 9 W; mains voltage: 220-240V/ 50/60Hz ; class of protection: I; Dimensions: Ø250 mm, total length approx. 3000mm; weight: 1.2 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	9 W	CRI	90
Total flux	650 lm	LOR	100%
Luminous efficacy	72 lm/W	Total power	9 W

Mounting mode

Pendant

Shape and measurements

Height: 9.84 in
Diameter: 9.84 in
Weight: 1.2 kg

Design

Material impression: Plastic

Electric

System power: 9 W
Voltage: 220-240 V AC
Appliance Class: I

Protection

IP: 20
Designation labels: CE