
Product data sheet


ALEA SPOT 641317.003.730 RZB



Series: Alea Spot Type of Protection: IP 20 Protection Class: II Voltage: 220 - 240 V / 50 - 60 Hz Pole: aluminium. Cover: plastic sphere, opal, satin finish. "Triple lamp; mains connection through pole to terminal in" "pole top; base plate: D 300. 4 mounting holes: D 10; pitch" circle for holes: D 230. Available Colours: black Type of Installation: Recessed ceiling mounting Dimensions: L 306, B 75, H 2 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Dimmable Bluetooth converter Safety Marks: F-mark Luminaire flux LED: 950Im System power: 8,2W Beam Angle: 60°/58° Number of fittings B10A: 82 Number of fittings B16A: 130 Inrush current: 5A Unified Glare Ratio: 16,7 EEC: A+

IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	8.2 W	CRI	80
Total flux	950 lm	LOR	100%
Luminous efficacy	116 lm/W	Total power	8.2 W

Mounting mode

Wall recessed

Shape and measurements

Length: 2.95 in Width: 12.05 in Height: 1.46 in

Adjustability

Fixed

Electric System power: 8.2 W Protection IP: 20