
Product data sheet


AVENUE METRO DIRECT/INDIRECT
POD_1250MM_WHITE
WHITECROFT



IP 20


1.25m - Modular linear LED system with a modern minimalist aesthetic for continuous or stand alone applications. TP(a) Pod optic for EN12464-1 compliant schemes. Create long lines and angles of light with a seamless aesthetic – as Whitecroft Lighting AVENUE METRO Emergency Lithium Output: 290lm

Light output 1 (integrated, emergency)




Lamp type	LED	CCT	4000 K
Nominal lamp power	1 W	CRI	1
Total flux	291 lm	LOR	100%
Luminous efficacy	291 lm/W	ULOR	13%
		Total power	1 W

Light output 2




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1702 lm	ULOR	13%
Luminous efficacy	113 lm/W	Total flux	1702 lm
CCT	4000 K	Total power	15 W
CRI	80		




1 x LED

Nominal lamp power	15 W	LOR	100%
Lamp flux	1702 lm	ULOR	13%
Luminous efficacy	113 lm/W	Total flux	1702 lm
CCT	3000 K	Total power	15 W
CRI	80		



1 x LED

Nominal lamp power	24 W	LOR	100%
Lamp flux	2966 lm	ULOR	13%
Luminous efficacy	121 lm/W	Total flux	2966 lm
CCT	4000 K	Total power	24.5 W
CRI	80		



1 x LED

Nominal lamp power	24 W	LOR	100%
Lamp flux	2791 lm	ULOR	13%
Luminous efficacy	114 lm/W	Total flux	2791 lm
CCT	3000 K	Total power	24.5 W
CRI	80		

Mounting mode

Pendant

Shape and measurements

Length: 3.15 in
Width: 49.21 in
Height: 3.94 in

Adjustability

Fixed, Height adjustable

Electric

System power: 16-25.5 W

Information regarding emergency functions

Supplementary emergency lighting
Emergency power supply: Single battery 3 h
Emergency sign: N/A

Protection

IP: 20