
Product data sheet


SINUS SUSP. 'Y' DI/ID SILVER SAT. 1530MM
R33Y153-9006E2840L3S
PLANLICHT



IP 40


low output LED 4000K CRI 90 113,5W 14783lm DALI https://katalog.planlicht.com/en-gb/fam-sinus/

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	14.19 W	CRI	90
Total flux	1848 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	14.19 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	14.19 W	CRI	90
Total flux	1848 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	14.19 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	14.19 W	CRI	90
Total flux	1848 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	14.19 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	14.19 W	CRI	90
Total flux	1848 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	14.19 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	14.19 W	CRI	90
Total flux	1848 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	14.19 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	14.19 W	CRI	90
Total flux	1848 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	14.19 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	14.19 W	CRI	90
Total flux	1848 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	14.19 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	14.19 W	CRI	90
Total flux	1848 lm	LOR	100%
Luminous efficacy	130 lm/W	Total power	14.19 W

Mounting mode

Pendant

Shape and measurements

Length: 60.24 in
Width: 60.24 in
Height: 3.94 in

Adjustability

Fixed

Electric

System power: 113.5 W

Protection

IP: 40