


Product data sheet

VERDA ASYM CL II 740 CLO CG
305061-566
FAGERHULT



Installation Luminaire for assembly on a post, with post top Ø 60 mm. Connection Supplied with 5 m 2x1,5 mm² connection cable (H07RN-F). Design Body, heat sink and cover in cast aluminium. Diffuser of impact resistant UV-stabilised polycarbonate. Ballast integrated in the luminaire. Reflector Symmetrical reflector in acrylic (PMMA) or asymmetrical reflector in sheet metal. Light distribution Symmetrical or asymmetrical. Dimming CLO (Constant Light Output) maintains the correct light from the luminaire for the duration of its service life. Other options for light control available on request. For more information, see Light control. Standard Colour Anthracite grey (Gris 900 Sablé). Miscellaneous Projected area: from the side 0.105 m², from above 0.058 m². Luminaire weight: 4.7 kg.

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	20 W	CRI	70
Total flux	2082 lm	LOR	100%
Luminous efficacy	104 lm/W	ULOR	18%
		Total power	20 W

Mounting mode

Pole top mounted

Electric

System power: 20 W

Shape and measurements

Length: 10.56 in
Width: 10.67 in
Height: 21.12 in

Protection

IP: 66

Adjustability

Fixed