# Product data sheet

LSRS8B/LSRSWM8B LED 8" SHALLOW ROUND CYLINDERS
LSR8B60D010 EC8B60935 8LBDW0WH
COOPER LIGHTING



IP 47

Mounting: high bay/low bay ceiling, wall, stem or aircraft cable, Spun aluminum housing; Spun aluminum reflectors, 5 color temperatures: 2700K, 3000K, 3500K, 4000K and 5000K CCT, CRI: 80, 90 or 97; D2W™ option from 3000K to 1850K, Lumens: 1,000-6,000; W2N Tunable White 2700K-6500K or 2000K-5000K, Colors: Matte Black, White, Bronze and Silver paint finishes, Standard 0-10V dimming down to 1%, ENERGY STAR® qualified, 5-year warranty, Integral or remote driver options

## Light output 1 (integrated)



| | | | |
|---|---|---|---|
| Lamp type | LED | CCT | 3500 K |
| Nominal lamp power | 59.5 W | CRI | 90 |
| Total flux | 5434 lm | LOR | 100% |
| Luminous efficacy | 91 lm/W | Total power | 59.5 W |

### Mounting mode

Ceiling recessed

### Shape and measurements

Height: 0.39 in
Diameter: 8.00 in

### Adjustability

Fixed

### Electric

System power: 59.5 W

### Protection

IP: 47