
Product data sheet


MULTILUME SLIM OPAL HB 600X600 RA 90 3000K DALI CLO
23404-402
FAGERHULT



IP 44

Installation Recessed mounting in ventilated or unventilated suspended ceilings. Two optional designs. VTB – for suspended ceilings with visible T-bars 15 or 24 mm. HB – for suspended ceiling with concealed T-bars/D-edge, symmetrical attachment of ceiling boards. Connection Connection in separate ballast box. The driver box can be positioned next to the luminaire. Snap-in terminal block 3x1,5mm2 (x2), through-wiring possible. 5x1,5mm2 (x2) when dimming. Can also be supplied with earthed mains cable and plug. Design Luminaire body of white enamelled sheet steel (RAL 9016). Louvre Opal plate in frosted UV stabil polystyrene. Miscellaneous Enclosure class IP 44 under suspended ceilings and IP 20 above suspended ceilings.

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	22 W	CRI	90
Total flux	2445 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	22 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 23.58 in
Width: 23.58 in
Height: 0.91 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 22 W

Protection

IP: 44