Product data sheet

TRIONA OPAL
312393.004.1.730
RZB



IP 20

Series: Triona Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 Hz Deckenbaldachin (D 260 mm, H 40 mm) Aluminium eloxiert. Mit Verbindungsleitung zwischen Leuchte und Deckenbaldachin. Mit 3-Punkt-Stahlseilabhängung, stufenlos höhenverstellbar. Abdeckung und Leuchtenrahmen Metall pulverbeschichtet. Diffusor aus Kunststoff (PMMA) opal. Betriebsgerät eingebaut. Leuchtmittel (LED) im Lieferumfang enthalten. Mit smart+free Bluetooth-Steuerbaustein zur drahtlosen Vernetzung und Bedienung von Leuchten. Available Colours: silver, metallic Type of Installation: Pendant Dimensions: D 1009, H 52 Lamp: LED Life time: 50000 h (L70/B10) Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Dimmable Bluetooth converter Safety Marks: F-mark Luminaire flux LED: 8700lm System power: 89W Beam Angle: 104° Number of fittings B10A: 6 Number of fittings B16A: 10 Inrush current: 40A Unified Glare Ratio: 20,4 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	89.4 W	CRI	80
Total flux	8700 lm	LOR	100%
Luminous efficacy	97 lm/W	Total power	89.4 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 2.05 in
Diameter: 39.72 in

Adjustability

Fixed

Electric

System power: 89.4 W

Protection

IP: 20