

# Product data sheet


ALFONS II FF LED (ASYM. WIDE BEAM)  
9.140.8228.01-3  
LEIPZIGER LEUCHTEN



IP  
66

recom. pole height: 6.00m – 12.00m light standards: low, medium and high lighting requirements lamp: incl. 1, 2, 3 or 4 FF II-X LED module(s), easy to replace colour temperature: 3.000K warm white or 4.000K neutral white LED gear: electronic driver, up to 100.000 hours; driver with integrated Constant Light Output (CLO) in order to keep the luminous flux at the same level over the entire lifetime LED life expectancy: up to 100.000 hours, 50.000 hours/ L100 for minimum maintenance costs due to an excellent thermal management light control: at extra cost: power reduction, dimming or CLEVER LIGHT optical system: directed light (multi layer) provided by an exchangeable, anti-aging lens technology light distribution: asymmetrical wide beam luminaire head: die cast aluminium, powder coated colour: DB 703; other colours on request glazing: flat, clear toughened glass glazing wiring: completely wired; via a plug and socket connector within the luminaire head; luminaire head to be hinged upward installation: for top or side entry; ASA 60 or ASA 76 to be ordered separately: • ASA 60 for side entry ø 48mm up to 60mm (0°, -5°, -10°, -15°) or for top entry ø 60mm (0°, 5°, 10°, 15°) • ASA 76 for top entry ø 76mm (0°, 5°, 10°) accessory: adapter ASA, column, pole accessories, wall bracket, cable – to be ordered separately application areas: parks, boulevards, schools, home for elderly people, hotels, factory premises, residential and local distribution roads, main streets, car parks, pedestrian and cycle lanes, holiday parks

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	63 W	CRI	70
Total flux	6503 lm	LOR	100%
Luminous efficacy	103 lm/W	Total power	63 W

## Mounting mode

Pole integrated, Pole top mounted

## Shape and measurements

Length: 29.13 in  
Width: 13.98 in  
Height: 7.68 in  
Weight: 11.5 kg

## Adjustability

Height adjustable

## Electric

System power: 63 W

## Protection

IP: 66