Product data sheet


LOUI BEAMLINE
921581.002.1.76
RZB



IP 20 IK 03


Series: LESS IS MORE BEAMLINE system Colour: traffic white, matt (RAL 9016) Length: 1121 mm Width: 57 mm Height: 75 mm Suspension length: 600-2000 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 90 Light source: LED Socket lamp2: Without base Colour temperature: 4000K System power: 63 W Rated luminous flux: 5600 lm Beam angle Down: 45° Luminous efficiency: 89 lm/W Control gear: Converter, dimmable, DALI Control gear: Converter, dimmable, DALI Protection class: I Type of protection: IP 20

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	31.5 W	CRI	90
Total flux	2800 lm	LOR	67%
Luminous efficacy	89 lm/W	ULOR	14%
		Total power	31.5 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	31.5 W	CRI	90
Total flux	2800 lm	LOR	67%
Luminous efficacy	89 lm/W	ULOR	14%
		Total power	31.5 W

Mounting mode

Pendant

Shape and measurements

Length: 2.24 in
Width: 44.13 in
Height: 2.95 in

Adjustability

Fixed

Electric

System power: 63 W

Protection

IP: 20
IK: 03

Design

Color of housing: White